



Gyro Wrap™

Many medium-volume car washes need a simple, rugged, and compact wrap-around brush capable of washing vehicles' fronts, sides, and back in a minimal footprint. The Gyro Wrap™ is the answer. Requiring just over 11 feet of space, the Gyro Wrap packs a lot of cleaning power into a small area.

Because side wash wheels take the most abuse, the Gyro Wrap is "Built to Tilt"™ through a full 360 degrees, minimizing the likelihood of damage to vehicle and equipment. The oversized socket joint uses a unique spherical bearing to create a maintenance-free 'Flex Head' at the top of the wrap.

This 'Flex Head' enables the Gyro Wrap to self-center, as the spinning wheel acts as its own gyrostabilizer. This means the Gyro Wrap will firmly hug the contour of each vehicle, washing the front, rear, and sides of each while making the wrap soft and forgiving on mirrors and antennas.

What's more, the simple socket joint design allows the integrated motor and gearbox to 'float' on the sturdy single-pieces shaft. This eliminates the troublesome couplings, three-piece shafts and U-joints that competitor's wraps rely on, all while helping maximize 'uptime' for the operator.

FEATURES & BENEFITS

Wrap-Around Washer

Provides superior cleaning results to vehicle fronts, sides, and backs

Built To Tilt Design

Enables wash wheels to tilt a full 360 degrees which greatly minimizes maintenance requirements and damage

Gyrostabilizer Positioning

Enables contoured cleaning performance around entire vehicle

Flex Head

Designed with oversized socket joints which provide safe, contoured cleaning results regardless of vehicle's size or shape

Compact Design

Is easy to incorporate into nearly any tunnel wash



REQUIREMENTS

Physical Examples

Bay Length Required	11' 2"
Component Height	9' 10"
Component Width	12' 2"
Vehicle Height Clearance	7' 6"
Vehicle Width Clearance	10' 7"

Utility Examples

Hydraulic Drive Option:	
Electrical	120 VAC
Hydraulic	4 GPM @ 900 PSI
Pneumatic	.3 CFM @ 90 PSI minimum and 120 PSI maximum
Water	3/4" feed @ 6 GPM @ 40 PSI
Electric Drive Option:	
Electrical	(2) 1 HP, 3 Phase 208/240/480 VAC
Pneumatic	.3 CFM @ 90 PSI minimum and 120 PSI maximum
Water	3/4" feed @ 6 GPM @ 40 PSI

COLOR OPTIONS

Choose from six vivid Neo-Text™ colors



Belanger

31840 Enterprise Drive, Bldg 5
Livonia, MI 48150 USA
belangerinc.com | 248-349-7010