



## Wave Full Side Washer™

Belanger's Wave Full Side Washer™ is specifically designed for targeted cleaning or polishing of vehicle sides, with a spin-cleaning action and the height to cover from the tops of the side windows all the way down to the rocker panels and wheels – even on today's larger vans, trucks and SUVs.

The closed-cell Neo-Tex™ foam provides the 'right touch' for full-side cleaning and polishing, while the self-adjusting shock and cylinder controls ensure the Wave Full Side Washer™ gently hugs the contour of each vehicle. As well, the adjustable wheel height meets the installation requirements of each tunnel.

To ensure an extended service life, the Wave Full Side Washer™ features a durable, corrosion-free aluminum framework and double-bearing arms for improved rigidity and smooth operation. A bulkhead utility hook-up makes installation easy, so you can start washing cars and making money – faster.

Like many Belanger wash components, the Wave Full Side Washer™ operates in a minimal amount of tunnel space – in this case, just seven feet are needed.

# Wave Full Side Washer™

## Contours Every Vehicle For Optimal Cleaning

Self-adjusting shock-and-cylinder arms self-adjust to best clean vehicle surfaces

## Installation Options To Integrate With Any Bay

Bulkhead utility hookups facilitate installation for easy integration in any wash bay

## Durable Construction For Extended ROI

Aircraft-grade aluminum frame and double-bearing arms deliver long service life

## Easily Adjust Operating Height Of Wash Wheels

Ensures cleaning coverage aligns with your facility's exact cleaning requirements



## Mount Freestanding Or To Other Components

Flexible mounting options save space, install faster and optimize your configuration

## Save Space; Uses Just 7 Feet Of Tunnel Length

Operates in only 84 inches of tunnel space, to maximize cleaning power per foot

## REQUIREMENTS

### Physical Examples

Tunnel Space Required	7'
Unit Height	9' 10"

### Utility Examples

#### Hydraulic Drive Option:

Electrical Requirements	120 VAC (for extend & retract)
Hydraulic Requirements	Approx. 5 GPM @ 900 PSI
Pneumatic Requirements	.3 CFM @ 90-PSI (minimum) to 120-PSI
Water Requirements	(2) 3/4" Feeds @ 6 GPM @ 40 PSI

#### Electric Drive Option:

Electrical Requirements	(2) 1HP, 3-Phase, 208/240/480 VAC
Pneumatic Requirements	.3 CFM @ 90-PSI (minimum) to 120-PSI
Water Requirements	(2) 3/4" Feeds @ 6 GPM @ 40 PSI

## COLOR OPTIONS

Choose from two vivid Neo-Tex™ wash media colors



Belanger  
1001 Doheny Court  
P.O. Box 5470  
Northville, MI 48167-5470 USA  
[belangerinc.com](http://belangerinc.com) | 248-349-7010

# BELANGER

*Inspired by You. Built by Belanger.*

PART OF  
**OPW**  
VEHICLE WASH SOLUTIONS  
a **DOVER** company