



## Whisper Wheel®

Designed as a dedicated horizontal surface washer, the Whisper Wheel® excels at cleaning hoods, roofs and trunk lids – all while providing a super-quiet customer experience. The uniquely shaped Neotex™ closed-cell foam wash 'fingers' provide superior wash penetration with vastly reduced in-car noise levels.

To deliver consistent cleaning results, regardless of vehicle size or shape, the Whisper Wheel features one of the industry's highest pivot points, along with a fully adjustable counterweight. This allows it to glide over customer vehicles with just the right pressure – maximizing cleaning effectiveness and safety.

Because the Whisper Wheel is a key contributor in achieving a clean car, it's built for maximum uptime and dependable operation. The fully-boxed 'I-Beam' aluminum frame is corrosion-free, rigid and strong. The sealed automotive-grade bearings are 'greased for life' and require zero maintenance.

When used with a Belanger controller, the available Auto-Retract option automatically senses open truck beds and safely lifts out of the way. This can make the Whisper Wheel a smart choice for operators who want the benefits of a top wash wheel that actively accommodates every vehicle.

## FEATURES & BENEFITS

### Superior Top Surface Washer

Delivers advanced contoured cleaning results to all horizontal surfaces including hoods, roofs, and trunk lids

### Air Cushion For Easy 'Fine Tuning'

Fingertip screw control for simple 'in-bay' adjustments



### Ultra-Safe Performance

Featuring the industry's highest pivot points, the Whisper Wheel glides over vehicles with its advanced counterweight design

### Robust, Proven 2-Leg Top Wheel Frame

The strongest foundation for reliable cleaning results

## REQUIREMENTS

### Physical Examples

Tunnel Space Required	9' 6"
Unit Height	11' 8"
Unit Width	12' 2"
Vehicle Height Clearance	7' 6"

### Utility Examples

#### Hydraulic Drive Option:

Electrical Requirements	3 Phase, 2HP Motor (optional) 110 VAC for Auto Retract option (with Belanger tunnel controller only)
Hydraulic Requirements	6 GPM @ 900 PSI
Pneumatic Requirements	.3 CFM @ 90 PSI minimum & 120 PSI maximum
Water Requirements	3/4" Feed @ 4 GPM @ 40 PSI

#### Electric Drive Option:

Electrical Requirements	1HP, 3-Phase, 208/240/480 VAC 110 VAC for Auto Retract option (with Belanger tunnel controller only)
Pneumatic Requirements	.3 CFM @ 90 PSI minimum & 120 PSI maximum
Water Requirements	3/4" Feed @ 4 GPM @ 40 PSI

## COLOR OPTIONS

Choose from two vivid Whisper Wheel colors



### Belanger

31840 Enterprise Drive, Bldg 5  
Livonia, MI 48150 USA  
[belangerinc.com](http://belangerinc.com) | 248-349-7010